

## The Avalon Difference

### Others

### Avalon International Aluminum Avalon-Exclusive Items in **Bold**

Extended Lip Strike Required	<b>No Extended Lip Strike Required</b>
Exact Throat of Wall Thickness	<b>Expanded Throat for Ease of Installation - 1/8" Added to All Throats</b>
Flush Glazed For Standard Throats Only	<b>Flush Glazed Using a Patented System For <b>Any</b> Throat 3-1/2" to 16-1/2"</b>
Trim Requires Notching	<b>Notching Never Required</b>
Sill Starter Channel or Blocking By Others For Sidelights	<b>No Starter Channel or Blocking Required - Quicker Field Installation</b>
Center-Glazed Sidelights	<b>Double-Glazed Sidelights, Offset Glazing and Center Glazing</b>
20-Minute Fire-Rated Sidelights	<b>Positive Pressure 45-Minute Fire Rated Sidelights, Borrowed Lights, &amp; Transoms</b>
Cut & Paste Shop Drawings	<b>Full AutoCAD Shops With Schedules, Elevations, Sectionals, &amp; Isometrics</b>
.062" Extrusion Thickness	.062" to .125" Extrusion Thickness
1/4" to 1/2" Glass Thickness	1/4" to 2-1/2" Glass Thickness <b>Integral Blinds Available</b>
Blade Door Stop	1" Wide Stop – No Closer Reinforcer Needed
Rudimentary Sound Attenuation Only	Sidelite System Independently Certified with an <b>STC Rating of 53</b>
1-1/2" or 2" Face	1-1/2", 2", 4", <b>6", and 8"</b> Face Available
CLASS II Clear Anodized	CLASS I or CLASS II Clear Anodized
Liquid Finish – Toxic Volatile Organic Compounds	Powder Coat – <b>NO VOC</b> – LEED credits EPD, MRC2, MRC3, MRC4, EQC2
Standard Hinge Backer	Heavy Duty Reinforced Hinge Backer – No Sagging or Squeaking
Glazing Lineals Typical	Pre-Cut and Boxed Per Opening
Standard Materials	Custom Design and Expediting Readily Available - Best in the Business
Standard Hardware Preps Only	Unlimited Custom Hardware: If it Fits in Our Frame, We Can Prep it